



LIVE-XC-LZ Series Low-impedance technology
Passive line array loudspeaker for high-quality speech and music transmission

Description:

The newly developed LIVE-XC series is the successor model to the Live-SM. The reproduction quality of speech and music is even more dynamic and pleasantly natural, even at high sound pressure levels. With newly developed 3.5" loudspeaker drivers, the LIVE-XC is in a higher class with exceptionally clear sound characteristics. With two separate Phoenix plug-in contacts for half and full power adjustment on the rear, this line speaker is very good for flexible use.

The harmonious exterior is identical to the highly successful ATLANTIC and ASCOLTO series. In all conceivable rooms, they show a perfect symbiosis in technology and shapely design.

For fixed installation, there is a female M6 thread on both the top and bottom, and a continuous groove for M6 threaded nuts along the entire length on the back. For flexible installation, a tiltable stand adapter for 35mm stands and extension cables with 5 and 10 metres are available.

Technische Details:

	LIVE-XC 40LZ	LIVE-XC 80LZ	LIVE-XC 120LZ
Rated power	40 Watt	80 Watt	120 Watt
Impedance	8 Ohm	8 Ohm	8 Ohm
Transmission range	140-18.000 Hz	140-18.000 Hz	140-18.000 Hz
Sound pressure 1W/1m	92 dB	96 dB	99 dB
Loudspeaker	6 x 3,5" wideband	10 x 3,5" wideband	14 x 3,5" wideband
Dimensions in mm (H x W x D)	612 x 90 x 96 mm	940 x90 x 96 mm	1.270 x 90 x 98 mm
Weight	3,2 kg	4,85 kg	6,15 kg
Colour	RAL 9010 white	RAL 9010 white	RAL 9010 white